




Manufacturers of BIO-SAFE Technology

Technical Data Sheet:

PAVACRYL

HARD COAT



Description:

PAVACRYL is an extra tough clear acrylic sealer especially designed for concrete and sandstone. Excellent resistance to heavy wear and ultra violet rays makes **PAVACRYL** ideal for external high traffic areas such as industrial and residential driveways, as well as paths, patios, pool surrounds, garages, shed.

Advantages:

- Suitable for internal and external use
- Finishes extremely hard for excellent wearing under heavy traffic
- High solids contents for ease of coverage of porous surfaces such as concrete and pavers
- Gives surface a glossy wet look, and enhances the natural colors of the surface.
- Seals against food, soils, grease, oil and inhibits staining
- Seals lime dust into concrete to prevent leaching and a constant need for sweeping
- Is easy to reseal without stripping
- Does not yellow externally
- Australian owned and manufactured in Australia

Characteristics:

Colour:	Clear
Weight:	0.90
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	4 – 8 sq m per lt (depending on porosity)

Recommendations:

Sandstone
Exposed aggregate
Plain concrete
Concrete Pavers
Stamped Concrete
Stencil Concrete

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*